

Model Number Series	FLUORES EVACB/Z07-1	EVDCYE30
Input	Input Voltage (Vac)	Single-Phase AC220V (L+N+PE) ±20%
	Input Current	32A
	Maximal efficiency	≥95%
	Power factor	≥95%
Output	AC Output Voltage Range	AC 220V
	Output Current	Single guns, 200A Each Gun
	Rated Power	7KW
User Interface	Cable Length	5m
	LED Display	4.3-Inch Touch Screen
	Communication	Bluetooth, 4G, Ethernet
	Payment Method	RFID Card, Password Charging, QR code Scanning
	Start Mode	Time Mode, Power Mode, Automatic Full Mode, Electricity Consumption Mode, Scheduled Charging Mode
	Emergency Stop	Supported
Safety	Ingress Protection	IP54
	Certification	TUV CE
	Electric Protection	Output Short Circuit Protection, Output Over-Voltage Protection, Output Under-Voltage Protection, Input Over-Voltage Protection, Input Under-Voltage Protection, AC Lack of Phase Protection, High Temperature Protection.
	Warranty	2 Years
	Management	OCPP 1.6 J
	Certification Standard	IEC-61851, IEC-62196
	Installation	Wall / Column Mounted (Optional)
Environment	Working Temperature	-20~+50°C
	Working Humidity	≤95%
	Working Altitude	≤2000M
	Dimension (mm)	1500*280*136
Package	Gross Weight	≤15KG
	External Package	Wooden Box

