

# VISION PLUS SERIES

## INTEGRATED DC CHARGING STATION



<b>Model Number Series</b>	EVDCYE160KW-2	EVDCYE160
<b>Input</b>	Input Voltage (Vac)	400Vac
	AC input frequency (Hz)	45~65
	Maximal efficiency	≥ 95%
	Power factor	≥ 95%
<b>Output</b>	Output voltage range (Vdc)	200V~1000V
	Output Current	Two guns, 200A Each Gun
	Rated Power	160KW
	Cable Length	5m
<b>User Interface</b>	LED Display	32-Inch Touch Screen
	Communication	Bluetooth, 4G, Ethernet
	Payment Method	RFID Card, Password Charging, QR code Scanning, Bank Card
	Start Mode	Time Mode, Power Mode, Automatic Full Mode, Electricity Consumption Mode, Scheduled Charging Mode
	Emergency Stop	Supported
<b>Safety</b>	Ingress Protection	IP54
	Electric Protection	Output Short Circuit Protection, Output Over-Voltage Protection, Output Under-Voltage Protection, Input Over-Voltage Protection, Input Under-Voltage Protection, AC Lack of Phase Protection, High Temperature Protection.
	Warranty	2 Years
	Management	OCPP1.6 or OCPP2.0
	Certification Standard	IEC-61851, IEC-62196
	Installation	Integrated
<b>Environment</b>	Working Temperature	-50 ~ +50°C
	Working Humidity	≤ 95%
	Working Altitude	≤ 2000M
	Dimension (mm)	1763*920*588
<b>Package</b>	Gross Weight	≈ 300KG
	External Package	Wooden Box