



# STARPATH SERIES

## INTEGRATED DC CHARGING STATION



|                            |                            |  |
|----------------------------|----------------------------|--|
| <b>Model Number Series</b> | STARPATH<br>EVDCYE400KW-2  | EVDCYE400  |
| <b>Input</b>               | Input Voltage (Vac)        | 380/400/480Vac   |
|                            | AC input frequency (Hz)    | 45~65  |
|                            | Maximal efficiency         | ≥95%   |
|                            | Power factor               | ≥95%   |
| <b>Output</b>              | Output voltage range (Vdc) | 200V~1000V   |
|                            | Output Current             | Two guns, 200A Each Gun  |
|                            | Rated Power                | 400KW  |
| <b>User Interface</b>      | Cable Length               | 5m   |
|                            | LED Display                | 7-Inch Touch Screen  |
|                            | Communication              | Bluetooth, 4G, Ethernet  |
|                            | Payment Method             | RFID Card, Password Charging, QR code Scanning, Bank Card  |
|                            | Start Mode                 | Time Mode, Power Mode, Automatic Full Mode, Electricity Consumption Mode, Scheduled Charging Mode  |
|                            | Emergency Stop             | Supported  |
| <b>Safety</b>              | Ingress Protection         | IP54   |
|                            | Certification              | TUV CE   |
|                            | Electric Protection        | Output Short Circuit Protection, Output Over-Voltage Protection, Output Under-Voltage Protection, Input Over-Voltage Protection, Input Under-Voltage Protection, AC Lack of Phase Protection, High Temperature Protection. |
|                            | Warranty                   | 2 Years  |
|                            | Management                 | OCPP 1.6 J   |
|                            | Certification Standard     | IEC-61851, IEC-62196   |
| <b>Environment</b>         | Installation               | Integrated   |
|                            | Working Temperature        | -50 ~ +50°C  |
|                            | Working Humidity           | ≤95%   |
|                            | Working Altitude           | ≤2000M   |
| <b>Package</b>             | Dimension (mm)             | 2150*950*650   |
|                            | Gross Weight               | ≤300KG   |
|                            | External Package           | Wooden Box   |