

Model Number Series	Fluores	EVACBYE07
Input	Input Voltage	Single-Phase AC220V (L+N+PE) ±20%
	AC input frequency	32A
	Energy efficiency	≥95%
	Power factor	≥0.8
Output	Output voltage range	AC 220V
	Output Current	Single gun, 32A
	Rated Power	7KW
User Interface	Cable Length	5m
	LED Display	7-Inch Touch Screen
	Communication	Bluetooth, 4G, Ethernet
	Payment Method	RFID Card, Password Charging , QR code Scanning , Bank Card
	Start Mode	Time Mode, Power Mode, Automatic Full Mode, Electricity Consumption Mode, Scheduled Charging Mode
	Emergency Stop	Supported
Safety	Ingress Protection	IP54
	Certification	TUV CE
	Safety Measures	Output Short Circuit Protection Output Over-Voltage Protection Output Under-Voltage Protection Input Over-Voltage Protection Input Under-Voltage Protection AC Phase-loss Protection Overheating Protection
	Warranty	2 Years
	Management	OCPP 1.6 J
	Standard	IEC-61851, IEC-62196
Environment	Installation	Wall / Column Mounted (Optional)
	Working Temperature	-20~+50℃
	Working Humidity	≤95%
	Working Altitude	≤2000M
Package	Dimension	1500*280*136MM
	Gross Weight	≤15KG
	External Package	Wooden Box

