



FULL SPECTRUM

护眼落地灯

FL01-1

- 3 CCT
3种颜色
- Full spectrum
全光谱照明
- Eye protection
保护眼睛

产品型号: Item Number	FL01-1
额定输入: Input Voltage	AC100V-240V
光效: lighting effect	52Lm/w
额定功率: Rated power	90W(上10W+下80W)450*0.2W/LED模块
额定电流: Rated current	2.5A
功率因数: Power factor	>0.9
使用光源: Light source	LED
显示指数: CRI(RA)	Ra>97
灯珠色温: Color Temperature	4000K
产品尺寸: Product Size	339*630*1964mm
工作环境: Working Temperature	0°C-+40°C
流明值: Luminous Flux	4048 LM

Short push-ON/OFF,DIM

FULL SPECTRUM

屏显护眼落地灯

FL01-2

- MODE INDICATOR**
1 2 3 4
- UP ON/OFF,DIM- Up Lighting**
ON/OFF within short-press;
brightness dimmable if long-press
- ON/OFF,DIM-Whole Lamp**
if short-press,ON/OFF for the whole lighting;if long-press,brightness dimmable
- DOWN ON/OFF,DIM-Down Lighting**
ON/OFF if short-press;brightness dimming if long-press
- MODE SELECT-Short-press M**
Change different 1-2-3-4modes

产品型号: Item Number	FL01-2
额定输入: Input Voltage	AC100V-240V
光效: lighting effect	52Lm/w
额定电流: Rated current	1A
功率因数: Power factor	>0.9
使用光源: Light source	LED
显示指数: CRI(RA)	Ra>97
灯珠色温: Color Temperature	4000K
产品尺寸: Product Size	339*630*1964mm
工作环境: Working Temperature	0°C-+40°C
流明值: Luminous Flux	4048 LM
额定功率: Rated power	96W(上16W+下80W) 492*0.195W/LED模块

- 3 CCT
3种颜色
- Full spectrum
全光谱照明
- Eye protection
保护眼睛





FULL SPECTRUM

全光谱落地灯

FL02-1


Full spectrum
全光谱照明

Eye-protection
保护眼睛

1 2 3 4

MODE INDICATOR



UP ON/OFF,DIM- Up Lighting

ON/OFF within short-press;
brightness dimmable if long-press


ON/OFF,DIM-Whole Lamp

if short-press,ON/OFF for the whole lighting;if long-press,brightness dimmable



DOWN ON/OFF,DIM-Down Lighting

ON/OFF if short-press;brightness dimming if long-press



MODE SELECT-Short-press M

Change different 1-2-3-4modes

产品型号: Item Number

FL02-1

额定输入: Input Voltage

AC100V-240V

光效: lighting effect

72.25Lm/W

额定功率: Input power

60W(上25W+下35W)216*0.116W+48*0.73/LED模块

额定电流: Rated current

0.75A

功率因数: power factor

>0.9

使用光源: light source

LED

显示指数: CRI(RA)

Ra>97

灯珠色温: Color Temperature

4000K

产品尺寸: Size

339X1027X1943mm

工作环境: Working Temperature

0°C~+40°C

流明值: luminous Flux

4466LM



FULL SPECTRUM

全光谱办公灯

FL02-2

Adjustable Rotation
可调节旋转

Full spectrum
全光谱照明

Eye protection
保护眼睛

1 2 3 4

MODE INDICATOR



UP ON/OFF,DIM- Up Lighting

ON/OFF within short-press;
brightness dimmable if long-press


ON/OFF,DIM-Whole Lamp

if short-press,ON/OFF for the whole lighting;if long-press,brightness dimmable



DOWN ON/OFF,DIM-Down Lighting

ON/OFF if short-press;brightness dimming if long-press



MODE SELECT-Short-press M

Change different 1-2-3-4modes

产品型号: Item Number

FL02-2

额定输入: Input Voltage

AC100V-240V

光效: lighting effect

72.25Lm/W

额定功率: Input power

60W(上25W+下35W)216*0.116W+48*0.73/LED模块

额定电流: Rated current

0.75A

功率因数: power factor

>0.9

使用光源: light source

LED

显示指数: CRI(RA)

Ra>97

灯珠色温: Color Temperature

4000K

产品尺寸: Size

127X1070X1133mm

工作环境: Working Temperature

0°C~+40°C

流明值: luminous Flux

4466LM

FULL SPECTRUM

屏显护眼落地灯

FL01-5



3 CCT
3种颜色




Full spectrum
全光谱照明



Eye protection
保护眼睛



Touch screen button
触摸屏按钮



Idler wheel
转向轮



Adjustable height
高度可调



Remote control
远程控制

产品型号: Item Number	FL01-5
额定输入: Input Voltage	100-240V
光效: lighting effect	52Lm/W
额定电流: Rated current	2.5A (LED) +1A (升降)
功率因数: power factor	>0.9
使用光源: light source	LED
显示指数: CRI(RA)	Ra>97
灯珠色温: Color Temperature	2700-6000K(CCT)
产品尺寸: Size	339X630X2050mm
流明值: luminous Flux	4048LM
升降速度: Lifting speed	25mm/S
升降范围: Lifting length	570mm
额定功率: Input power	96W(up 16W +Down 80W) 480PCS LED*0.21W+35W升降驱动



MODE INDICATOR



UP ON/OFF, DIM- Up Lighting
ON/OFF within short-press;
brightness dimmable if long-press



ON/OFF,DIM-Whole Lamp
if short-press,ON/OFF for the whole lighting;if long-press,brightness dimmable



DOWN ON/OFF,DIM-Down Lighting
ON/OFF if short-press;brightness dimming if long-press




MODE SELECT-Short-press M
Change different 1-2-3-4modes

FULL SPECTRUM

屏显护眼落地灯

FL04-1



- UP ON/OFF,DIM

DOWN ON/OFF DIM

产品型号: Item Number	FL04-1
额定输入: Input Voltage	AC100V-240V
光效: lighting effect	72.25Lm/W
额定电流: Rated current	0.75A
功率因数: power factor	>0.9
使用光源: light source	LED
显示指数: CRI(RA)	Ra>97
灯珠色温: Color Temperature	4000K
产品尺寸: Size	339X975X1940mm
工作环境: Working Temperature	0°C+40°C
流明值: luminous Flux	4466LM
额定功率: Input power	60W(上25W+下35W) 216*0.116W+48*0.73/LED模块



Full spectrum
全光谱照明



Eye protection
保护眼睛

FULL SPECTRUM

全光谱办公灯

FL04-2

SWITCHES ON BOTH SIDES

UP ON/OFF,DIM;

DOWN ON/OFF,DIM

产品型号: Item Number FL04-2
 额定输入: Input Voltage AC100V-240V
 光效: lighting effect 72.25Lm/W
 额定功率: Input power 120W(上50W+下70W)2/LED模块
 额定电流: Rated current 0.75A
 功率因数: power factor >0.9
 使用光源: light source LED
 显示指数: CRI(RA) Ra>97
 灯珠色温: Color Temperature 4000K
 产品尺寸: Size 338*1945*1945mm
 工作环境: Working Temperature 0°C-+40°C
 流明值: luminous Flux 8932LM



Full spectrum
全光谱照明

Eye protection
保护眼睛

FULL SPECTRUM

全光谱办公灯

FL04-3



UP ON/OFF,DIM;

DOWN ON/OFF,DIM

产品型号: Item Number FL04-3
 额定输入: Input Voltage AC100V-240V
 光效: lighting effect 72.25Lm/W
 额定功率: Input power 60W(上25W+下35W)216*0.116W+48*0.73/LED模块
 额定电流: Rated current 0.75A
 功率因数: power factor >0.9
 使用光源: light source LED
 显示指数: CRI(RA) Ra>97
 灯珠色温: Color Temperature 4000K
 产品尺寸: Size 118*975*1133mm
 工作环境: Working Temperature 0°C-+40°C
 流明值: luminous Flux 4466LM


Adjustable Rotation
可调节旋转

Full spectrum
全光谱照明

Eye protection
保护眼睛

FULL SPECTRUM
全光谱办公灯

FL04-4



产品型号: Item Number FL04-4
额定输入: Input Voltage AC100V-240V
光效: lighting effect 72.25Lm/W
额定功率: Input power 120W(上50W+下70W)2/LED模块
额定电流: Rated current 0.75A
功率因数: power factor >0.9
使用光源: light source LED
显示指数: CRI(RA) Ra>97
灯珠色温: Color Temperature 4000K
产品尺寸: Size 118*1945*1133mm
工作环境: Working Temperature 0°C-+40°C
流明值: luminous Flux 8932LM



Adjustable Rotation
可调节旋转




Full spectrum
全光谱照明



Eye protection
保护眼睛

FULL SPECTRUM
屏显护眼落地灯

FL03-1



UP ON/OFF,DIM
DOWN ON/OFF,DIM



产品型号: Item Number FL03-1
额定输入: Input Voltage AC100V-240V
光效: lighting effect 122 Lm/W
额定功率: Input power 90W(上60W+下30W)LED模块
额定电流: Rated current 0.45A
功率因数: power factor >0.9
使用光源: light source LED
显示指数: CRI(RA) Ra>97
灯珠色温: Color Temperature 4000K
产品尺寸: Size 580*338*1950mm
工作环境: Working Temperature 0°C-+40°C
流明值: luminous Flux 11000LM(上7700+下3300)



Full spectrum
全光谱照明



Eye protection
保护眼睛